

# Porto Cement.

E: sales@qcg.co.nz | W: www.qcg.co.nz | P: 0800 525 585



Porto Cement's muted cementitious texture, and natural, undulating surface creates a soft minimalist effect. The perfect tile to create a refined and peaceful environment in your interior spaces.

**PRODUCT TYPE:** Glazed Porcelain

**COLOURS:** See colour options overleaf

**SIZES<sup>(1)</sup>:** 600x600

**SURFACES:** Matt

**EDGES:** Rectified

**USAGE:** Suitable for floors and walls

**TECHNICAL INFO:** See overleaf

**VARIATION<sup>(3)</sup>:** V2

**WARRANTY<sup>(3)</sup>:** 15 Years

**ORIGIN:** China

(1) Sizes are nominal and may include a grout joint. (2) Variation is an inherent property of tiles and stone. (3) If further details are required regarding our warranty or terms please contact our team on sales@qcg.co.nz or 0800 525 585

# Porto Cement.

E: sales@qcg.co.nz | W: www.qcg.co.nz | P: 0800 525 585

## COLOURS:












## SIZES:



TECHNICAL CHARACTERISTICS	STANDARD	VALUE
---------------------------	----------	-------

Compliant with standards EN 14411 annex G group Bla. Compliant with standards ISO 13006 annex G group Bla.

	Water absorption	EN ISO 10545-3	<0.5%
	Frost Resistance	EN ISO 10545-12	✓
	Chemical resistance	EN ISO 10545-13	✓
	Size variation	EN ISO 10545-2	-
	Thickness	-	9.5mm
	Hardness (MOHS)	EN 101	-
	Faces	-	8
	Breaking Strength	EN ISO 10545-4	-
		<b>Anti-slip</b>	<b>Natural</b>
	Slip Resistance	DIN 51130 (R) *	-
		AS/NZS 4586:2013 (SRV)	R10
		Average BP (P)	-