

Industry.

E: sales@qcg.co.nz | W:www.qcg.co.nz | P: 0800 525 585



Industry is a popular collection of Italian porcelain tiles with a striking, undulating lappato surface. This easy care and unique surface disperses and reflects light, creating a sense of luxe and great design. With matching anti-slip surfaces, the Industry collection is perfectly suited to today's modern home environments where an indoor, outdoor flow is essential to quality home design.

PRODUCT TYPE: Glazed Coloured Porcelain

COLOURS: See colour options overleaf

SIZES(1): 600×600 / 900×900

SURFACES: Lappato

EDGES: Rectified

USAGE: Floors and Walls

TECHNICAL INFO: See overleaf

VARIATION(3): V2

WARRANTY(3): 15 Years

ORIGIN: Italy

(1) Sizes are nominal and may include a grout joint. (2) Variation is an inherent property of tiles and stone. (3) If further details are required regarding our warranty or terms please contact our team on sales@qcg.co.nz or 0800 525 585



Industry.

E: sales@qcg.co.nz | **W:**www.qcg.co.nz | **P:** 0800 525 585

COLOURS:







Silver Platinum

Iron

SIZES:

600x600

TECHNICAL CHARACTERISTICS	STANDARD	VALUE
TECHNICAL CHARACTERISTICS	SIANDARD	VAI

Compliant with standards EN 14411 annex G group Bla. Compliant with standards ISO 13006 annex G group Bla.

♠ Water absorption EN ISO 10545-3 <0.5%				
▲ Chemical resistanceEN ISO 10545-13✓✔ Size variationEN ISO 10545-2+/- 0.1%▼ Thickness-10mm❤ Hardness (MOHS)EN 1015♣ Slip resistanceAS/NZS 4586:2013-♣ Breaking StrengthEN ISO 10545-4-		Water absorption	EN ISO 10545-3	<0.5%
✓ Size variationEN ISO 10545-2+/- 0.1%I Thickness-10mm❤ Hardness (MOHS)EN 1015✓ Slip resistanceAS/NZS 4586:2013-I Breaking StrengthEN ISO 10545-4-	*	Frost Resistance	EN ISO 10545-12	✓
T Thickness - 10mm ♦ Hardness (MOHS) EN 101 5 ★ Slip resistance AS/NZS 4586:2013 - ★ Breaking Strength EN ISO 10545-4 -	T	Chemical resistance	EN ISO 10545-13	✓
W Hardness (MOHS) EN 101 5 ★ Slip resistance AS/NZS 4586:2013 - ★ Breaking Strength EN ISO 10545-4 -	٧,	Size variation	EN ISO 10545-2	+/- 0.1%
Slip resistance AS/NZS 4586:2013 - Breaking Strength EN ISO 10545-4 -	Ī	Thickness	-	10mm
	*	Hardness (MOHS)	EN 101	5
	<u>*</u>	Slip resistance	AS/NZS 4586:2013	-
Faces	<u>†</u>	Breaking Strength	EN ISO 10545-4	-
	f	Faces	-	-